

Specification

CPU	S3C6410 (ARM11 667MHz)
Memory	256MB DRAM / 256MB Flash
Display	2.4" TFT Color LCD
Sensor	Optical / 500 DPI
Authentication Type	Fingerprint, Password, RF card
Time	1:1 < 0.2 sec.
	1:N < 1 sec. (4,000 templates)
Template Capacity	20,000 templates (2 templates / 1 finger, 10,000 User)
Log Capacity	100,000 logs
Communication	TCP/IP, Wiegand In/Out (26/34bit)
Lock	Deadbolt, EM Lock, Door Strike, Automatic Door
Environment	-20~60°C / < RH 90%
Certificate	KC, CE, FCC
Dimensions	75(W) x 182.5(H) x 39.2(D) mm

Features

- 2.4" TFT Color LCD
 - Fingerprint Image Quality Check
 - Notice / Status bar
 - Wallpaper with company logo
- Touch Keypad
- USB Memory Slot
 - Easy data transfer using USB memory stick
- Superior Matching Engine
 - 1st rank in FVC (Fingerprint Verification Competition)
- Function Key
 - User-defined functions (F1~F4)
 - Clock In/Clock Out/Absence/Return
- Multifactor Authentication
 - Fingerprint, RF card, Password

Product Family

Model	Description
SW250-S	Standard (Fingerprint, Password)
SW250-M	Standard, High Frequency Card (13.56MHz) -Mifare
SW250-R	Standard, Low Frequency Card (125kHz) -HID, EM

System Configuration



S/W Package

>> AccessManager Pro.

Item	Contents
Component	AccessServer / AccessManager / DBMS
Max. Accessing Terminal	2,000 EA
Max. Remote Client	16 (Access Manager)
OS	Windows XP or higher
Max. User	100,000 User (in the Server)
DBMS	MS SQL 2005 or higher, MS SQL Express 2005 or higher
Similar Fingerprint Check	O

eNBioAccess-T3



Kimaldi Electronics

Crta. Rubí 292 B Pol. Ind. Can Guítard
08228 - Terrassa (Barcelona) Spain
Tel. 937 361 510 Fax. 937 361 511
kimaldi@kimaldi.com

Kimaldi Lusa

portugal@kimaldi.com

