

## INDUSTRY AND LOGISTICS



# Logi Tag™



### DISCREET RFID TAGS THAT WITHSTAND LIQUID IMMERSION, HIGH PRESSURE CONDITIONS AND EXTREME TEMPERATURES

- **Inconspicuous** – Compact form factors conceal easily in textile assets, hand tools or small equipment.
- **Durable** – Resistant to extreme temperature, chemicals, fluids, industrial detergents and high pressure.
- **Powerful** – Rapid, accurate asset identification and data storage, with anti-collision functionality for simultaneous processing of multiple items.

#### TECHNOLOGY HIGHLIGHTS:

- LF 125 kHz, HF 13.56 MHz / NFC or UHF near-field
- 64-bit UID; up to 8KB read-write user memory, crypto options (Vigo™ 2K)
- Anti-collision, multi-read capable (HF)
- High chemical and mechanical resistance
- Temperature resistant up to 347° F (175° C)
- Options for mounting on metal or non-metal surfaces, or radiation resistant FRAM

#### APPLICATION AREAS:

- **ASSET TRACKING AND LOGISTICS**
  - Inventory
  - Tools and small equipment
- **LAUNDRY**
  - Automated accounting of cleaning
  - Automated sorting and inventory
  - Clothing, uniforms
  - Commercial laundry
  - Owner identification
- **MEDICAL AND HEALTH**
  - Hospital laundry
  - Medical and surgical accessories

HID Global Logi Tag™ transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications.

The smallest Logi Tag discs are ideal for tagging industrial tools and small equipment. Among the smallest HF tags available, Logi Tag 081 and 121 units are assembled using patented DBond™ Vigo™ technology that enables HID Global to produce tags in thinner, smaller formats without compromising performance. They mount with industrial adhesives, with options for metal or non-metal surfaces. Logi Tag HF transponders are NFC Tag Type 5 compliant when formatted with NDEF data structure. Alternatively, LogiTag 180 is a RAIN® RFID near-field UHF coin to be used with standard EPC-Gen2 equipment.

As part of a commercial laundry logistics system, Logi Tag discs ensure accurate item counting and documentation, while enabling automatic billing and real-time inventory control.












Logi Tag discs enable medical facilities automatically track clothing, linens, rags, surgical sponges, and life-saving equipment.

Effective tracking of reusable assets and verification of cleaning and sterilization procedures ensures better patient and staff safety through improved infection control.

Logi Tag discs are easily sewn into the hem or seam of a garment, uniform, napkin, tablecloth or runner. They may also be affixed to custodial supplies, such as mats, mops, washrags and towels or are used to tag the hangers to automate laundry workflows. The Logi Tag Button 162 transponder is indistinguishable from ordinary buttons, and can be sewn onto clothing with standard stitching equipment and processes.

Logi Tag transponders empower logistics applications via radio frequency identification (RFID) technology, enabling more accurate, efficient asset management and inventory control processes. Logi Tag discs are compliant with standard RFID readers and modules, and are ATEX certified for safe use in potentially explosive environments. LogiTag 161 is also available in a radiation resistant, high-memory FRAM option for most demanding application scenarios.

# SPECIFICATIONS

	120			160	081	121	121 OM	161		162 Button	180	
												
<b>Base Model Number</b>	624115	612115	601115	601106	6A9081-010	6A9121-010 (Vigo 1K), 6D0121-010 (Vigo 2K), 629121-010 (SLIX)	6A9121-310 (Vigo 1K), 6D0121-310 (Vigo 2K), 629121-310 (SLIX)	629108-411 629108-401 (ICODE SLIX)	634108-410 (F-Mem 2K), 6D1108-410 (F-Mem 8K)	629110-411	6H2112	
<b>ELECTRONIC</b>												
<b>Operating Frequency</b>	125 kHz				13.56 MHz						860-960 MHz (Worldwide)	
<b>Chip Type</b>	Hitag S	Q5	Unique		Vigo or ICODE SLIX			ICODE SLIX2	F-Mem	ICODE SLIX2	Monza R6-P	
<b>Memory</b>	2048 bit EEPROM	264 bit EEPROM	64 bit read-only		1024 or 2048 bit (Vigo) or 896 bit UM (ICODE SLIX)			2560 bit UM	2 or 8 Kbyte FRAM	2560 bit UM	28/96 bit EPC, 32/64 bit UM	
<b>Anti-Collision</b>	Yes			Yes			Yes					
<b>Reading Distance [4 W reader]</b>					Proximity			Up to 13.4 in (34 cm)			Proximity	
<b>PHYSICAL</b>												
<b>Dimensions</b> (for exact dimension tolerances, request drawing)	Ø 0.5 × 0.1 in (12 x 2 mm)			Ø 0.6 × 0.1 in (16 x 3 mm)	Ø 0.31 × 0.1 in (8 x 2 mm)	Ø 0.49 × 0.1 in (12.4 x 2 mm)		Ø 0.6 × 0.1 in (16 x 3 mm)		Ø 0.6 × 0.1 in (16 x 2.5 mm)	Ø 0.6 × 0.1 in (18 x 3 mm)	
<b>Mounting Method</b>	Sew into, glue, embed									Sew on	Sew into, glue, embed	
<b>Embeds In / Affixes To</b>	Clothing and Textiles, non-metal Tools and Boxes				Non-metal	Metal	Clothing and Textiles, non-metal Tools and Boxes				Non-metal	
<b>Housing Material</b>	PPS with epoxy potting		Epoxy	ABS with epoxy potting	PPS with epoxy potting			PPS			Polycarbonate	
<b>Color</b>	Black						White				Transparent Blue	
<b>Weight</b>	0.02 oz (0.6 g)		0.04 oz (1.1 g)	0.004 oz (0.11 g)	0.01 oz (0.4 g)			0.04 oz (1.0 g)		0.03 oz (0.85 g)	0.02 oz (0.75 g)	
<b>CHEMICAL AND MECHANICAL RESISTANCE</b>												
<b>Water</b>	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h						IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h				IP68, 6.6 ft (2 m) x 24 h	
<b>Pressure</b>	70 bars, 3 min isostatic						70 bars, 3 min isostatic					
<b>Withstands Exposure To</b>	Bleach (5%), caustic soda (pH 11), formic acid (pH7), gasoline, HCL (10%), oil, petroleum, salt water				Fuel B, mineral and vegetable oils, petroleum, salt mist		Hydrogen peroxide (5%), industrial laundry detergent (pH 10 - 11), neutralizing agent, perchlorethylen (100%)					
<b>Environmental Test Conditions</b>	68° F (20° C), 100 h											
<b>Vibration</b>	IEC 68.2.6 [10g, 10...2000Hz, 3 axis, 2.5 h]											
<b>Shock</b>	IEC 68.2.29 [40g, 18ms, 6 axis, 2000 x]											
<b>Drop Test</b>	100 x 6 ft (1.8 m)											
<b>Axial/Radial Force</b>	800 N / 500 N, 10 sec		1000 N / 1000 N, 10 sec	800 N / 500 N, 10 sec			800 N / 500 N, 10 sec			1000 N / 1000 N, 10 sec		
<b>THERMAL</b>												
<b>Storage</b>	-40° to +266° F (-40° to 130° C), 1000 h		-13° to +248° F (-25° to +120° C), 1000 h	-40° to +194° F (-40° to +90° C), 1000 h			-40° to +185° F (-40° to +85° C), 1000 h					
<b>Operating</b>	-13° to +185° F (-25° to +85° C)	-40° to +185° F (-40° to +85° C)			-40° to +194° F (-40° to +90° C)		-13° to 185° F (-25° to +85° C)				-40° to +185° F (-40° to +85° C)	
<b>Shock/Fatigue</b>	68° to +320° F (20°C to +160°C), 100 x 5 min with 30 sec transition			-40° to +194° F (-40°C to +90°C), 100 x 5 min with 30 sec transition			68° to +356° F (20°C to +180°C), 300 x 5 min with 30 sec transition			-40° to +185° F (-40°C to +85°C), 100 x 5 min with 30 sec transition		
<b>Peak</b>	320° F (160° C), 35 h						248° F (120° C), 100 h, 428° F (220° C), 30 sec		248° F (120° C), 100 h	284° F (140° C), 100 h		
<b>Spin dryer / tunnel finisher (set point)</b>			347° F (175° C), 100 x 10 min	347° F (175° C), 100 x 10 min								
<b>OTHER</b>												
<b>Standards</b>	EN 60079-0:2009, EN 60079-11:2007, EN 50303:2001				EN 60079-0:2009, EN 60079-11:2007, EN 50303:2001 ISO 15693, ISO 18000-3, NFC Tag Type 5 (optional)						UHF EPC Class 2 Gen 2, ISO 18000-6C	
<b>Options</b>	Custom printed logo			Custom printed logo, Vigo chip 1.6K			Custom embossed logo, UID laser engraving			Laser engraving		
<b>Box Size</b>	2,500 pcs		2,000 pcs	5,000 pcs	2,500 pcs			2,000 pcs				
<b>Warranty</b>	2 Years											