



## ISO Card Unique

<b>Description</b>		<b>Proximity ISO card, flexible Card design to suit to most 125 kHz proximity systems.</b>		
<b>IC type:</b>	UNIQUE 64 bits RF/64 ASK Manchester			
<b>Physical:</b>	Thickness:	0.76 mm	± 0.08 mm	
	Length:	85.60 mm	± 0.12 mm	
	Width:	53.98 mm	± 0.05 mm	
	Weight:	5.60 g	± 0.50 g	
	Color:	White / white		
<b>Printing:</b>	Both side are full printable with offset, thermo-transfer and dye sublimation printing.			
<b>Slots:</b>	3 different positions for slots are available.			
<b>Contact module:</b>	Customer may embed a contact module at ISO position.			
<b>Magnetic stripe:</b>	Optional HICO 2750 Oe magnetic stripe in ISO position.			
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz	
<b>Material:</b>	PVC, white / white (Glossy).			
<b>Thermal:</b>	-35°C and +50°C	(-30°F and +122°F)	according to <b>ISO 7816</b> .	
<b>Resistance:</b>	The card is designed to resist common stress known from access control and time attendance systems.			
<b>Specials:</b>	Different HICO and LOCO magnetic stripe are available on request as well as customized logo prints and holograms.			